

VDVFE-1G81D12T

CAMERA	
Image Sensor	1/2.8" 5.14 Megapixel Sony CMOS Sensor
ISP	EYENIX EN781
Scanning System	Progressive Scan
S/N Ratio	More than 50dB
Video Output Resolution	1MP (16:9) - 1280 X 720 25/30fps 2MP (16:9) - 1920 X 1080 25/30fps 4MP (16:9) - 2560 X 1440 25/30fps
Video Output Mode	AHD TVI CVI CVBS or EX-SDI CVBS
Minimum Illumination	Color : 0.15 Lux B&W : 0.015 Lux IR LED on : 0 Lux
Coaxial Communication	AHD : Pelco-C (ACP), TVI : Hikvision-C, CVI : HD-CVI or OSD Control
LENS & IR LED	
Lens Type	Fixed Board Lens
Focal Length	f = 3.6mm
Aperture Ratio	F = 2.0
IR LED	850nm X 12pcs
CAMERA FUNCTIONS	
OSD	Built in
Electronic Shutter Speed	Auto / Flickerless / Manual
	NTSC : 1/30 sec ~ 1/30,000 sec
	PAL : 1/25 sec ~ 1/25,000 sec
Brightness	1 ~ 20 Step
AGC	1 ~ 10 Step
SENS Up	Off / X2 ~ X32
BLC	Off / HLC / BLC / WDR
Day & Night	Auto / Color / B&W / Extern
White Balance	Auto / Auto EXT / Preset / Manual
DNR	Off / Low / Middle / High
Sharpness	0 ~ 10 Step
Mirror	Off / On
Flip	Off / On
ACE (D-WDR)	Off / Low / Middle / High
Defog	Off / On
Shading	Off / On
Privacy Masking	Off / On
Motion Detection	24-Mask (Box - 16 / Polygon - 8)
Language	English, Korean, Japanese, Chinese
GENERAL	
Power Source	DC12V (+/-) 10%
Power Consumption	IR LED Off : 150mA IR LED on : 350mA
Operating Temperature	-10°C ~ + 50°C / 0% ~ 90% RH
Dimension	63mm (H) X 95mm Diameter