

IP - 5MP BOX Camera

VN1X-5N60E




Features

- 1/2.8" Sony STARVIS CMOS Sensor
- Progressive Scan
- Total Number of Pixels: 2704 x 2104 (5.69 MP)
- 5 MP, 1944p @ 30 fps
- H.265, H.264, MJPEG
- IP Network
- Web Server Built-in
- 3DNR / Digital WDR
- ONVIF Compatibility
- PoE support

Physical

- Standard Box Type
- Aluminium Die Casting
- SD Card Slot Optional

Dimensions



CAMERA

Image Sensor	1/2.8" Sony CMOS Sensor - IMX335
Total Pixels	2704 x 2104 (5.69 MP)
Effective Pixels	2592 x 1944 (5.03 MP)
Scanning Mode	Progressive Scan
Minimum Illumination	Color: 0.05 Lux @ F1.2 B&W: 0.005 Lux @ F1.2
S/N Ratio	More than 50dB (AGC off)

LENS & IR LED

Lens Type	-
Focal Length	-
Aperture Ratio	-
IR LED	-

CAMERA FUNCTIONS

Wide Dynamic Range	Digital WDR
Day and Night Mode	Automatic, Day, Night, External Sync
Noise Reduction	2D-NR, 3D-NR
Auto Exposure Mode	Automatic, Manual
Shutter Speed Control	1/100,000 - 1/2 sec
Auto White Balance	Auto, Outdoor, Shade, Clear sky, Fluorescent light, Light Bulb, Manual
Digital Zoom	16x
BLC	On / Off
HLC	On / Off
Tamper	On / Off

NETWORK

Video Compression	H.264 / H.265 / MJPEG
Video Resolution	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440 480 x 360
Video Frame Rate	2592 x 1944 @ up to 30 fps
Video Streaming	Simultaneously H.265, H.264, MJPEG, Independent Frame Rate and Bandwidth Control, VBR/CBR Mode
Protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, TRCP, DHCP, ARP, Zeroconf
Client Software	Built in Web, ONVIF Compatible 3rd Party VMS
Security	Multi user Authority, IP Filtering, HTTPS
Max User Connection	10 Users
Network Time Sync	Synchronize Computer / NTP Server, Manual
Software Reset	Restart, Reset, Factory Default
Remote Upgrader	Using Web Browser
Ethernet	RJ-45 (10/100 Base-T)
SDK Support	API, ONVIF Profile S/T Compliant

GENERAL

Power Source	DC 12V (+/-) 10%, PoE IEEE802.3af, Class3
Power Consumption	240mA
Operating Temperature	-10°C - +50°C / 0% - 90% RH
Dimension	121.56mm x 67mm x 65mm